Application No.: 10/599314 Case No.: 59598US005

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

- 1. (Currently amended) A mold comprising:
- a support comprising a composite material of a <u>thermoplastic polyolefin</u> polymeric material and 20 to 70 percent volume based on the composite of a <u>glass fiber</u> reinforcing material blended with the polymeric material, and
- a shape-imparting surface layer disposed on the support; wherein the mold has a coefficient of hydroscopic swelling of less than 5 ppm per percent relative humidity.
- 2. (original) The mold of claim 1 wherein the mold is flexible.
- 3. (original) The mold of claim 1 wherein the shape-imparting surface layer is microstructured.
- 4. (original) The mold of claim 3, wherein the microstructured surface comprises a groove pattern.
- 5. (original) The mold of claim 3, wherein the microstructured surface comprises a protrusion pattern.
- 6-8. (cancelled)
- 9. (Currently Amended) The mold of claim [[$\frac{8}{2}$] $\frac{1}{2}$ wherein said polyolefin is a polypropylene or a cycloolefin.
- 10. (Currently Amended) The mold of claim 1, wherein said composite thermoplastic polyolefin polymeric material comprises polypropylene and glass fiber.

Application No.: 10/599314 Case No.: 59598US005

11. (original) The mold of claim 1, wherein said shape-imparting layer comprises a cured resin composition.

- 12. (original) The mold of claim 11, wherein said cured resin composition is photocured.
- 13. (original) The mold of claim 3, wherein the microstructured surface is a protrusion pattern corresponding to barrier ribs for a back plate of a plasma display panel.

14-16. (cancelled)

- 17. (Previously presented) The mold of claim 1, wherein the coefficient of hydroscopic swelling is less than 3 ppm per percent relative humidity.
- 18. (Previously presented) The mold of claim 1, wherein the coefficient of hydroscopic swelling is less than 1 ppm per percent relative humidity.
- 19. (original) A method of making a microstructured article comprising providing the mold of claim 1;

disposing a curable material between a substrate and the shape-imparting microstructured surface layer of the mold;

curing the curable material; and removing the mold.

20-23. (Canceled)